# EH1D2G48TFA0 (03030NXH)

### Datasheet

Get a Quote



### Overview

The EH1D2G48TFA0 provides forty-eight GE electrical ports for data transmission and line-rate switching. It performs concurrent data forwarding using a distributed data plane.

#### **Quick Specification**

#### Table 1 shows the quick specification.

Model	EH1D2G48TFA0
Part Number	03030NXH
Description	48-port 10/100/1000BASE-T interface card (FA, RJ45)
Level-1 category	Interface Card
Dimensions (H x W x D) [mm(in.)]	394.7 mm x 426.8 mm x 35.1 mm (15.5 in. x 16.8 in. x 1.4 in.)
Weight [kg(lb)]	2.50 kg (5.51 lb)
Maximum power consumption [W]	48 W
Environmental Parameters	Operating temperature: 0°C to 45°C (32°F to 113°F)
	Operating relative humidity: 5% RH to 95% RH (noncondensing)
	Storage temperature: $-40^{\circ}$ C to $+70^{\circ}$ C ( $-40^{\circ}$ F to $+158^{\circ}$ F)
	Storage relative humidity: 5% RH to 95% RH (noncondensing)

#### Figure 1 shows the appearance of EH1D2G48TFA0.



#### **Get More Information**

Do you have any question about the EH1D2G48TFA0 (03030NXH)?

Contact us now via info@hi-network.com.



## EH1D2G48TFA0 (03030NXH)

Datasheet



## Specification

EH1D2G48TFA0 Specification		
Basic Information		
EH1D2G48TFA0	EH1D2G48TFA0	
Part Number	03030NXH	
Description	48-port 10/100/1000BASE-T interface card (FA, RJ45)	
Level-1 category	Interface Card	
Technical Specifications		
Dimensions (H x W x D) [mm(in.)]	394.7 mm x 426.8 mm x 35.1 mm (15.5 in. x 16.8 in. x 1.4 in.)	
Weight [kg(lb)]	2.50 kg (5.51 lb)	
Maximum power consumption [W]	48 W	
Environmental Parameters	Operating temperature: 0°C to 45°C (32°F to 113°F)	
	Operating relative humidity: 5% RH to 95% RH (noncondensing)	
	Storage temperature: -40°C to +70°C (-40°F to +158°F)	
	Storage relative humidity: 5% RH to 95% RH (noncondensing)	

### Want to Buy



## **Contact HI-NETWORK.COM For Global Fast Shipping**

HongKong Office Tel: +00852-66181601 HangZhou Office Tel: +0086-571-86729517 Email: info@hi-network.com Skype: echo.hinetwork WhatsApp Business: +8618057156223

