Datasheet



Get a Quote

Overview

Building on high-performance hardware and the Huawei Versatile Routing Platform (VRP), the S5720-LI series switches support intelligent stack (iStack), flexible Ethernet networking, and diversified security control. They support multiple Layer 3 routing protocols and provide high performance and service processing capabilities. The S5720-LI series switches are ideal for various scenarios such as enterprise campus network access and gigabit to the desktop.

Quick Specification

Model	S5720-28X-PWR-LI-ACF
Part Number	98010595
Memory (RAM)	512 MB
Flash	512 MB in total. To view the available flash memory size, run the display version command.
РоЕ	Supported
Weight with packaging [kg(lb)]	5.9 kg (13.01 lb)
Dimensions (H x W x D)	Basic dimensions (excluding the parts protruding from the body): 43.6 mm x 442.0 mm x 314.9 mm (1.72 in. x 17.4 in. x 12.39 in.) Maximum dimensions (the depth is the distance from ports on the front panel to the parts protruding from the rear panel): 43.6 mm x 442.0 mm x 323.9 mm (1.72 in. x 17.4 in. x 12.75 in.)




Datasheet



Product Details:

Appearance:



1)	Twenty-four PoE+ 10/100/1000BASE-T ports
2	Four 10GE SFP+ ports
3	One PNP button
4	One console port
(5)	One USB port
6	Ground screw
7	RPS socket
8	Jack for AC power cable locking strap
9	AC socket

The Accessories for S5720-28X-PWR-LI-ACF:

Recommended models:

Model	Description
OMXD30000	Huawei Optical Transceiver OMXD30000, SFP+, 10G, Multi-mode Module (850nm, 0.3km, LC)
SFP-GE-LX-SM1310	Optical Transceiver, eSFP, GE, Single-mode Module (1310nm, 10km, LC)
OMXD30009	Transceiver, QSFP+, 1310nm, 41.25Gbps, -7dBm, 2.3dBm, -11.5dBm, LC, SMF, 10
ESFP-GE-SX-MM850	Optical Transceiver, eSFP, GE, Multi-mode Module (850nm,0.5km, LC)



Datasheet



Get more information:

Do you have any question about the S5720-28X-PWR-LI-ACF 98010595?

Contact us now via e-mail: info@hi-network.com

Specific Data Sheet:

Part Number	98010595
Model	S5720-28X-PWR-LI-ACF
Memory (RAM)	512 MB
Flash	512 MB in total. To view the available flash memory size, run the display version command.
Mean time between failures (MTBF)	41 years
Mean time to repair (MTTR)	2
Availability	> 0.99999
Service port surge protection	Common mode: ±7 kV
Power supply surge protection	±6 kV in differential mode, ±6 kV in common mode
Dimensions (H x W x D)	Basic dimensions (excluding the parts protruding from the body): 43.6 mm x 442.0 mm x 314.9 mm (1.72 x 17.4 in. x 12.39 in.) Maximum dimensions (the depth is the distance from ports on the front panel to the parts protruding from rear panel): 43.6 mm x 442.0 mm x 323.9 mm (1.72 in. x 17.4 in. x 12.75 in.)
Weight (with packaging)	5.9 kg (13.01 lb)
Stack ports	Twenty-four 10/100/1000BASE-T ports and four 10G SFP+ ports
RTC	Not supported
RPS	Supported
РоЕ	Supported
Rated voltage range	100 V AC to 240 V AC, 50/60 Hz
Maximum voltage range	90 V AC to 264 V AC, 47 Hz to 63 Hz
Maximum power consumption (100% throughput, full speed of fans)	Not providing the PoE function: 45 W 100% PoE loads: 984 W (PoE: 739.2 W)
Typical power consumption (30% of traffic load) Tested according to ATIS standard EEE enabled No PoE power consumption	33 W
Operating temperature	0°C to 45°C (32°F to 113°F) at an altitude of 0-1800 m (0-5906 ft.)
Short-term operating temperature	-5°C to +55°C (23°F to 131°F) at an altitude of 0-1800 m (0-5906 ft.)
Storage temperature	-40°C to +70°C (-40°F to +158°F)
Noise under normal temperature (27°C, sound	< 59.1 dB(A)





Datasheet

power)	
Relative humidity	5% to 95%, noncondensing
Operating altitude	0-5000 m (0-16404 ft.)
	EMC certification
Certification	Safety certification
	Manufacturing certification

Want to Buy

Get a Quote









Learn More about Hi-Network

Search our Resource Library

 $\underline{Follow} \ us \ on \ Linked In$

Contact for Sales or Support

Contact HI-NETWORK.COM For Global Fast Shipping

HongKong Office Tel: +00852-66181601 HangZhou Office Tel: +0086-571-86729517

Email: info@hi-network.com Skype: echo.hinetwork

WhatsApp Business: +8618057156223

