

Datasheet

[Get a Quote](#)

Overview

Huawei S5720-28X-SI delivers high performance of switching capacity and powerful layer 3 routing capabilities, such as OSFP/OSPFv3, BGP/BGP4+, ISIS/ISISv6, and provides voice, video and data services, helping enterprises build an integrated full service network with high availability and low latency. The S5720-28X-SI builds with 24 Gigabit Ethernet ports and 4 SFP+ 10G uplinks and it can be used as access or aggregation switches on campus networks or access switches in data centers. The S5720-28X-SI supports intelligent stacking (iStack). Multiple S5720-SI can be connected with stack cables to set up a stack, which functions as a virtual switch. A stack consists of a master switch, a backup switch, and several slave switches. The backup switch takes over services when the master switch fails, reducing service interruption time. Stacks support intelligent upgrade so that users do not need to change the software version of a switch when adding it to a stack. The iStack function allows users to connect multiple switches with stack cables to expand system capacity.


Quick Specification

Model	S5720-28X-SI-AC
Part Number	02350DLT
Memory (RAM)	512 MB
Flash	512 MB in total. To view the available flash memory size, run the display version command.
PoE	Not supported
Weight with packaging [kg(lb)]	9.1 kg (20.06 lb)
Dimensions (H x W x D)	Basic dimensions (excluding the parts protruding from the body): 44.4 mm x 442.0 mm x 424.7 mm (1.75 in. x 17.4 in. x 16.72 in.) Maximum dimensions (the depth is the distance from ports on the front panel to the handle on the rear panel): 44.4 mm x 442.0 mm x 451.8 mm (1.75 in. x 17.4 in. x 17.79 in.)

Datasheet

Product Details:

Appearance:



①	Twenty 10/100/1000BASE-T ports
②	Four combo ports (10/100/1000BASE-T + 100/1000BASE-X)
③	Four 10GE SFP+ ports
④	One ETH management port
⑤	One console port
⑥	One USB port
⑦	Ground screw
⑧	ESN label
⑨	Power module slot 2
⑩	Power module slot 1

The Accessories for S5270-28X-SI-AC:

Recommended elements:

Model	Description
FE-SFP Optical Transceiver	
SFP-FE-SX-MM1310	Optical Transceiver, SFP, 100M/155M, Multi-mode Module(1310nm, 2km, LC)
eSFP-FE-LX-SM1310	Optical Transceiver, eSFP, 100M/155M, Single-mode Module(1310nm, 15km, LC)

Datasheet

S-SFP-FE-LH40-SM1310	Optical Transceiver, eSFP, FE, Single-mode Module(1310nm, 40km, LC)
GE-SFP Optical Transceiver	
eSFP-GE-SX-MM850	Optical Transceiver, eSFP, GE, Multi-mode Module(850nm, 0.55km, LC)
SFP-GE-LX-SM1310	Optical Transceiver, eSFP, GE, Single-mode Module(1310nm, 10km, LC)
S-SFP-GE-LH40-SM1310	Optical Transceiver, eSFP, GE, Single-mode Module(1310nm, 40km, LC)
S-SFP-GE-LH40-SM1550	Optical Transceiver, eSFP, GE, Single-mode Module(1550nm, 40km, LC)
10G-SFP+ Optical Transceiver	
SFP-10G-USR	10GBase-USR Optical Transceiver, SFP+, 10G, Multi-mode Module(850nm, 0.1km, LC)
OMXD30000	Optical Transceiver, SFP+, 10G, Multi-mode Module(850nm, 0.3km, LC)
OSX010000	Optical Transceiver, SFP+, 10G, Single-mode Module(1310nm, 10km, LC)
GE Copper Transceiver	
SFP-1000BaseT	Electrical Transceiver,SFP,GE,Electrical Interface Module(100m,RJ45)

Compare to Similar Items:

Product Code	S5720-28X-SI-AC	S5720-52X-SI-AC
Switching Capacity	336 Gbit/s	336 Gbit/s
Forwarding Performance	96 Mpps	132 Mpps
Downlink Interfaces	24 Ethernet 10/100/1,000 ports, 4 of which are dual-purpose 10/100/1,000 or SFP	48 Ethernet 10/100/1,000 ports
Uplink Interfaces	4 x 10 Gig SFP+	4 x 10 Gig SFP+

Get more information:

Do you have any question about the S5720-28X-SI-AC 02350DLT?

Contact us now via e-mail: info@hi-network.com

Specific Data Sheet:

Part Number	02350DLT
Model	S5720-28X-SI-AC
Memory (RAM)	512 MB
Flash	512 MB in total. To view the available flash memory size, run the display version command.
Mean time between failures (MTBF)	82.4 years
Mean time to repair (MTTR)	2
Availability	> 0.99999



Datasheet

Service port surge protection	Common mode: ± 6 kV
Power supply surge protection	Using AC power modules: ± 6 kV in differential mode, ± 6 kV in common mode Using DC power modules: ± 1 kV in differential mode, ± 2 kV in common mode
Dimensions (H x W x D)	Basic dimensions (excluding the parts protruding from the body): 44.4 mm x 442.0 mm x 424.7 mm (1.75 in. x 17.4 in. x 16.72 in.) Maximum dimensions (the depth is the distance from ports on the front panel to the handle on the rear panel): 44.4 mm x 442.0 mm x 451.8 mm (1.75 in. x 17.4 in. x 17.79 in.)
Weight (with packaging)	9.1 kg (20.06 lb)
Stack ports	GE electrical ports and 10GE SFP+ optical ports except combo ports on the front panel
RTC	Supported
RPS	Not supported
PoE	Not supported
Rated voltage range	100 V AC to 240 V AC, 50/60 Hz -48 V DC to -60 V DC
Maximum voltage range	90 V AC to 264 V AC, 47 Hz to 63 Hz -36 V DC to -72 V DC
Maximum power consumption (100% throughput, full speed of fans)	37.5 W
Typical power consumption (30% of traffic load) - Tested according to ATIS standard - EEE enabled - No PoE power consumption	22.3 W
Operating temperature	0°C to 45°C (32°F to 113°F) at an altitude of 0-1800 m (0-5906 ft.)
Short-term operating temperature	-5°C to +50°C (23°F to 122°F) at an altitude of 0-1800 m (0-5906 ft.)
Storage temperature	-40°C to +70°C (-40°F to +158°F)
Noise under normal temperature (27°C, sound power)	< 52 dB(A)
Relative humidity	5% to 95%, noncondensing
Operating altitude	AC power modules configured: 0-5000 m (0-16404 ft.) DC power modules configured: 0-2000 m (0-6562 ft.)
Certification	EMC certification Safety certification Manufacturing certification



S5720-28X-SI-AC (02350DLT)



Datasheet

Want to Buy

Get a Quote



[Learn More](#) about Hi-Network



[Search](#) our Resource Library



[Follow](#) us on LinkedIn



Contact for [Sales or Support](#)

Contact HI-NETWORK.COM For Global Fast Shipping

HongKong Office Tel: +00852-66181601

HangZhou Office Tel: +0086-571-86729517

Email: info@hi-network.com

Skype: [echo.hinetwork](#)

WhatsApp Business: +8618057156223