

Get a Quote

Overview

GLC-LH-SM is the 1000BASE-LX/LH SFP for Both Multimode and Single-Mode Fibers. The 1000BASE-LX/LH SFP, compatible with the IEEE 802.3z 1000BASE-LX standard, operates on standard single-mode fiber-optic link spans of up to 10 km and up to 550 m on any multimode fibers. When used over legacy multimode fiber type, the transmitter should be coupled through a mode conditioning patch cable.

Quick Specification

Product	Wavelength (nm)	Fiber Type	Core Size (μm)	Modal Bandwidth (MHz* Km)	Operating Distance (m)
1000BASE-LX/LH	1310	MMF	62.5	500	550 (1,804 ft)
			50	400	550 (1,804 ft)
			50	500	550 (1,804 ft)
		SMF	-	-	10,000 (32,821 ft)

Product Details:

The Front Panel:



Compare To Similar Items:

Item	GLC-LH-SMD	GLC-LH-SM
Product Category	1000BASE-LX/LH	1000BASE-LX/LH
Wavelength (nm)	1310	1310
DOM Function	Yes Digital Diagnostics Monitoring This feature gives the end user the ability to monitor real-time parameters of the SFP, such as optical output power, optical input power, temperature, laser bias current, and transceiver supply voltage.	No

Get more information:

Do you have any question about the GLC-LH-SM?

Contact us now via e-mail: info@hi-network.com

Specific Data Sheet:

Product Name	GLC-LH-SM
Form Factor	SFP
TX Wavelength	1310 nm
Reach	10 Km
Cable Type	SMF
Rate Category	1000 Base
Interface Type	LX
DDM	No
Connector Type	Dual-LC

Want to Buy

Get a Quote



[Learn More](#) about Hi-Network



[Search](#) our Resource Library



[Follow](#) us on LinkedIn



Contact for [Sales or Support](#)

Contact HI-NETWORK.COM For Global Fast Shipping

HongKong Office Tel: +00852-66181601

HangZhou Office Tel: +0086-571-86729517

Email: info@hi-network.com

Skype: [echo.hinetwork](https://www.skype.com/people/echo.hinetwork)

WhatsApp Business: +8618057156223