



Get a Quote

Overview

Cisco Catalyst 2960-Plus 24 Ports LAN Lite Switches, supporting 24 x 10/100 ports, are designed for branches, conventional office workspaces, and infrastructure networks.

Quick Specification

Part Number	WS-C2960+24TC-S
Enclosure Type	1RU
Feature Set	LAN Lite
Uplink Interfaces	2 (SFP or 1000BASE-T)
Ports	24 x 10/100 Ethernet Interfaces
Forwarding Performance	16Gbps
RAM	128 MB
Flash Memory	64 MB
Dimensions	45.0 cm x 24.2 cm x 4.4 cm
Package Weight	7.73 Kg



Get a Quote



Product Details:

The Front Panel:



①	Switch LEDs
②	Mode button
③	24*10/100 ports
④	Dual-purpose ports

The Back Panel:



①	RJ-45 console port
②	Fan exhaust
③	RPS connector





Get a Quote

④	AC power connector
---	--------------------

Accessories For WS-C2960+24TC-S:

Modules and Cables:

Model	Description
CAB-CONSOLE-RJ45	Console Cable 6ft with RJ45 and DB9F
GLC-LH-SM	GE SFP, LC connector LX/LH transceiver
GLC-SX-MMD	1000BASE-SX SFP transceiver module, MMF, 850nm, DOM

Compare To Similar Items:

Models	Description
Cisco WS-C2960+24TC-S	Cisco Catalyst 2960 Plus 24 port 10/100M + 2 T/SFP LAN Lite
Cisco WS-C2960+24TC-L	Cisco Catalyst 2960 Plus 24 10/100 + 2T/SFP LAN Base
Cisco WS-C2960+48TC-S	Catalyst 2960 Plus 48 ports 10/100 + 2 T/SFP, LAN Lite
Cisco WS-C2960+48TC-L	Catalyst 2960 plus 48 port 10/100 + 2 T/SFP, LAN Base
Cisco WS-C2960+24PC-S	Catalyst 2960 Plus 24 10/100 PoE + 2 T/SFP, LAN Lite

Get more information:

Do you have any question about WS-C2960+24TC-S?

Contact us now via e-mail: info@hi-network.com

Specific Data Sheet:

Product Number	WS-C2960+24TC-S
Uplink Interfaces	2 (SFP or 1000BASE-T)
Cisco IOS Software Feature Set	LAN Lite
Available PoE Power	None
RAM	128 MB
Flash Memory	64 MB
Forwarding bandwidth	16 Gbps
Maximum active VLANs	64





Get a Quote

VLAN IDs available	4K
Maximum transmission unit (MTU) - L3 packet	9000 bytes
Jumbo frame - Ethernet frame	9018 bytes
Forwarding Rate: 64-Byte L3 Packets, Millions of packets per second	6.5
Width	17.7 Inches (45.0 cm)
Depth	9.52 Inches (24.2 cm)
Height	1.73 Inches (4.4 cm)
Package Weight	17.04 Pounds (7.73Kg)
Weight	8 lb (3.6 Kg)
Package Weight	17.04 lb (7.73 Kg)
Operating temperature up to 5000 ft (1500 m)	23°F to 113°F
Operating temperature up to 10,000 ft (3000 m)	23°F to 104°F
Short-term exception at sea level*	23°F to 131°F
Short-term exception up to 5000 feet (1500 m)*	23°F to 122°F
Short-term exception up to 10,000 feet (3000 m)*	23°F to 113°F
Short-term exception up to 13,000 feet (4000 m)*	23° to 104°F
Storage temperature up to 15,000 feet (4573 m)	-13° to 158°F
Operating altitude	Up to 10,000 feet
Storage altitude	Up to 13,000 feet
Operating relative humidity	10% to 95% noncondensing
Storage relative humidity	10% to 95% noncondensing
Sound Pressure, dBA	Typical, LpAm: 33 Maximum, LpAD: 36
Sound Power, dbA	Typical, LwA: 43 Maximum, LwAD: 46
MTBF in thousands of hours	667
Ethernet Interfaces	10BASE-Tports:RJ-45connectors,2-pairCategory3,4,or5unshieldedtwtisted-pair(UTP)cabling 100BASE-TXports:RJ-45connectors,2-pairCategory5UTPcabling 1000BASE-Tports:RJ-45connectors,4-pairCategory5UTPcabling 1000BASE-TSFP-basedports:RJ-45connectors,4-pairCategory5UTPcabling
Indicator LEDs	Per-port status :Link integrity ,disabled ,activity ,speed, and full duplex System status, Port Status ,RPS ,link duplex ,and link speed
Console	Cisco Catalyst console cables: CAB-CONSOLE-RJ45Consolecable6ft.withRJ-45
Power	The internal power supply is an auto-ranging unit and supports input voltages between 100 and 240V AC. Use the supplied AC power cord to connect the AC power connector to an AC power outlet. The Cisco RPS connector offers connection for an optional Cisco RPS 2300 that uses AC input and supplies DC output to the switch. Only the Cisco RPS 2300 (model PWR-RPS2300) should be attached to the redundant-power-system receptacle.





Get a Quote

Management	<p>BRIDGE-MIB</p> <p>CISCO-CABLE-DIAG-MIB</p> <p>CISCO-CDP-MIB</p> <p>CISCO-CLUSTER-MIB</p> <p>CISCO-CONFIG-COPY-MIB</p> <p>CISCO-CONFIG-MAN-MIB</p> <p>CISCO-DHCP-SNOOPING-MIB</p> <p>CISCO-ENTITY-VENDORTYPE-OID-MIB</p> <p>CISCO-ENVMON-MIB</p> <p>CISCO-ERR-DISABLE-MIB</p> <p>CISCO-FLASH-MIB</p> <p>CISCO-FTP-CLIENT-MIB</p> <p>CISCO-IGMP-FILTER-MIB</p> <p>CISCO-IMAGE-MIB</p> <p>CISCO-IP-STAT-MIB</p> <p>CISCO-LAG-MIB</p> <p>CISCO-MAC-NOTIFICATION-MIB</p> <p>CISCO-MEMORY-POOL-MIB</p> <p>CISCO-PAGP-MIB</p> <p>CISCO-PING-MIB</p> <p>CISCO-POE-EXTENSIONS-MIB</p> <p>CISCO-PORT-QOS-MIB</p> <p>CISCO-PORT-SECURITY-MIB</p> <p>CISCO-PORT-STORM-CONTROL-MIB</p> <p>CISCO-PRODUCTS-MIB</p> <p>CISCO-PROCESS-MIB</p> <p>CISCO-RTTMON-MIB</p> <p>CISCO-SMI-MIB</p> <p>CISCO-STP-EXTENSIONS-MIB</p> <p>CISCO-SYSLOG-MIB</p> <p>CISCO-TC-MIB</p> <p>CISCO-TCP-MIB</p> <p>CISCO-UDLDP-MIB</p> <p>CISCO-VLAN-IFTABLE</p> <p>RELATIONSHIP-MIB</p> <p>CISCO-VLAN-MEMBERSHIP-MIB</p> <p>CISCO-VTP-MIB</p> <p>ENTITY-MIB</p> <p>ETHERLIKE-MIB</p> <p>IEEE8021-PAE-MIB</p> <p>IEEE8023-LAG-MIB</p> <p>IF-MIB</p> <p>INET-ADDRESS-MIB</p> <p>OLD-CISCO-CHASSIS-MIB</p> <p>OLD-CISCO-FLASH-MIB</p>
------------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------





Get a Quote

	<p>OLD-CISCO-INTERFACES-MIB OLD-CISCO-IP-MIB OLD-CISCO-SYS-MIB OLD-CISCO-TCP-MIB OLD-CISCO-TS-MIB RFC1213-MIB RMON-MIB RMON2-MIB SNMP-FRAMEWORK-MIB SNMP-MPD-MIB SNMP-NOTIFICATION-MIB SNMP-TARGET-MIB SNMPv2-MIB TCP-MIB UDP-MIB ePM MIB</p>
<p>Standards</p>	<p>IEEE 802.1D Spanning Tree Protocol IEEE 802.1p CoS Prioritization IEEE 802.1Q VLAN IEEE 802.1s IEEE 802.1w IEEE 802.1X IEEE 802.1ab (LLDP) IEEE 802.3ad IEEE 802.3af IEEE 802.3ah (100BASE-X single/multimode fiber only) IEEE 802.3x full duplex on 10BASE-T, 100BASE-TX, and 1000BASE-T ports IEEE 802.3 10BASE-T IEEE 802.3u 100BASE-TX IEEE 802.3ab 1000BASE-T IEEE 802.3z 1000BASE-X RMON I and II standards SNMP v1, v2c, and v3</p>
<p>RFC compliance</p>	<p>RFC 768 - UDP RFC 783 - TFTP RFC 791 - IP RFC 792 - ICMP RFC 793 - TCP RFC 826 - ARP RFC 854 - Telnet RFC 951 - Bootstrap Protocol (BOOTP) RFC 959 - FTP RFC 1112 - IP Multicast and IGMP RFC 1157 - SNMP v1 RFC 1166 - IP Addresses</p>





Get a Quote

	<p>RFC 1256 - Internet Control Message Protocol (ICMP) Router Discovery</p> <p>RFC 1305 - NTP</p> <p>RFC 1492 - TACACS+</p> <p>RFC 1493 - Bridge MIB</p> <p>RFC 1542 - BOOTP extensions</p> <p>RFC 1643 - Ethernet Interface MIB</p> <p>RFC 1757 - RMON</p> <p>RFC 1901 - SNMP v2C</p> <p>RFC 1902-1907 - SNMP v2</p> <p>RFC 1981 - Path MTU Discovery for IPv6</p> <p>FRC 2068 - HTTP</p> <p>RFC 2131 - DHCP</p> <p>RFC 2138 - RADIUS</p> <p>RFC 2233 - IF MIB v3</p> <p>RFC 2373 - IPv6 Aggregatable Adrs</p> <p>RFC 2460 - IPv6</p> <p>RFC 2461 - IPv6 Neighbor Discovery</p> <p>RFC 2462 - IPv6 Autoconfiguration</p> <p>RFC 2463 - ICMP IPv6</p> <p>RFC 2474 - Differentiated Services (DiffServ) Precedence</p> <p>RFC 2597 - Assured Forwarding</p> <p>RFC 2598 - Expedited Forwarding</p> <p>RFC 2571 - SNMP Management</p> <p>RFC 3046 - DHCP Relay Agent Information Option</p> <p>RFC 3376 - IGMP v3</p> <p>RFC 3580 - 802.1X RADIUS</p>
Voltage (Autoranging)	100 to 240 VAC
Current (Amperes)	0.4 - 0.2
Frequency	50 to 60Hz
Power Rating (kVA)	0.02
DC Input Voltages (RPS Input)	2A at 12V
Power Consumption	<p>0% traffic: 18.6</p> <p>10% traffic: 18.7</p> <p>100% traffic: 19.1</p> <p>ATIS weighted average: 18.8</p>
Regulatory Compliance	Products should comply with CE Marking per directives 2004/108/EC and 2006/95/EC
Safety	<p>UL 60950-1 Second Edition</p> <p>CAN/CSA-C22.2 No. 60950-1 Second Edition</p> <p>EN 60950-1 Second Edition</p> <p>IEC 60950-1 Second Edition</p> <p>AS/NZS 60950-1</p>
EMC - Emissions	<p>47CFR Part 15 (CFR 47) Class A</p> <p>AS/NZS CISPR22 Class A</p>





Get a Quote

	CISPR22 Class A EN55022 Class A ICES003 Class A VCCI Class A EN61000-3-2 EN61000-3-3 KN22 Class A CNS13438 Class A
EMC - Immunity	EN55024 CISPR24 EN300386 KN24
Environmental	Reduction of Hazardous Substances (RoHS) including Directive 2011/65/EU

Want to Buy

Get a Quote



[Learn More](#) about Hi-Network



[Search](#) our Resource Library



[Follow](#) us on LinkedIn



Contact for [Sales or Support](#)

Contact HI-NETWORK.COM For Global Fast Shipping

HongKong Office Tel: +00852-66181601

HangZhou Office Tel: +0086-571-86729517

Email: info@hi-network.com

Skype: echo.hinetwork

WhatsApp Business: +8618057156223

