

Get a Quote

Overview

AIR-AP2802I-N-K9 is one of the Cisco Aironet 2800 Series Access Points. This 2800 series, delivering new 802.11ac Wave 2 standard, is ideal for large enterprise organizations that rely on Wi-Fi to engage with customers. The Series is a hands-off product that's intelligent enough to make decisions based on end-device activities and usage. AIR-AP2802I-N-K9 provides internal antenna and N regulatory domain.

Quick Specification

Product Code	AIR-AP2802I-N-K9
Frequency band and 20-MHz operating channels	N (N regulatory domain): - 2.412 to 2.462 GHz; 11 channels - 5.180 to 5.320 GHz; 8 channels - 5.745 to 5.825 GHz; 5 channels
Antenna	Internal Antenna
Features	<ul style="list-style-type: none"> - 4x4 MU-MIMO with three spatial streams - MRC - 802.11ac Beamforming - 20-, 40-, 80, 160-MHz channels - PHY data rates up to 5.2 Gbps - Packet aggregation: A-MPDU (Tx/Rx), A-MSDU (Tx/Rx) - 802.11 DFS - CSD support
Interfaces	<ul style="list-style-type: none"> - 2 x 100/1000BASE-T autosensing (RJ-45) - Management console port (RJ-45) - USB 2.0 (enabled via future software)
System memory	<ul style="list-style-type: none"> - 1024 MB DRAM - 256 MB flash
Dimensions (W x L x H)	8.66 x 8.68 x 2.17 in.
Net Weight	3.53 lb (1.6 kg)

Product Details:

The Front Panel:



Notes:

There is a LED in the face of this AP.

Compare to Similar Items

Models	AIR-AP2802I-N-K9	AIR-AP2802I-Q-K9
Frequency band and 20-MHz operating channels	N (N regulatory domain): - 2.412 to 2.462 GHz; 11 channels - 5.180 to 5.320 GHz; 8 channels - 5.745 to 5.825 GHz; 5 channels	Q (Q regulatory domain): - 2.412 to 2.472 GHz; 13 channels - 5.180 to 5.320 GHz; 8 channels - 5.500 to 5.700 GHz; 11 channels
Antenna	Internal Antenna	Internal Antenna
Features	<ul style="list-style-type: none"> - 4x4 MU-MIMO with three spatial streams - MRC - 802.11ac Beamforming - 20-, 40-, 80, 160-MHz channels - PHY data rates up to 5.2 Gbps - Packet aggregation: A-MPDU (Tx/Rx), A-MSDU (Tx/Rx) - 802.11 DFS - CSD support 	<ul style="list-style-type: none"> - 4x4 MU-MIMO with three spatial streams - MRC - 802.11ac Beamforming - 20-, 40-, 80, 160-MHz channels - PHY data rates up to 5.2 Gbps - Packet aggregation: A-MPDU (Tx/Rx), A-MSDU (Tx/Rx) - 802.11 DFS - CSD support

Get more information:

Do you have any question about the AIR-AP2802I-N-K9?

Contact us now via e-mail: info@hi-network.com



Specific Data Sheet:

Software	<p>Cisco Unified Wireless Network Software Release 8.2.111.0 or later</p> <p>Cisco IOS®XE Software Release 16.3</p>
Supported wireless LAN controllers	<p>Cisco 2500 Series Wireless Controllers, Cisco Wireless Controller Module for ISR G2, Cisco Wireless Services Module 2 (WiSM2) for Catalyst®6500 Series Switches, Cisco 5500 Series Wireless Controllers, Cisco Flex® 7500 Series Wireless Controllers, Cisco 8500 Series Wireless Controllers, Cisco Virtual Wireless Controller</p> <p>Cisco Catalyst 3850 Series Switches, Cisco Catalyst 3650 Series Switches</p> <p>Cisco Mobility Express</p>
802.11n version 2.0 (and related) capabilities	<ul style="list-style-type: none"> • 4x4 MIMO with three spatial streams • Maximal ratio combining (MRC) • 802.11n and 802.11a/g beamforming • 20- and 40-MHz channels • PHY data rates up to 450 Mbps (40 MHz with 5 GHz) • Packet aggregation: A-MPDU (Tx/Rx), A-MSDU (Tx/Rx) • 802.11 dynamic frequency selection (DFS) • Cyclic shift diversity (CSD) support
802.11ac Wave 1 capabilities	<ul style="list-style-type: none"> • 4x4 MIMO with three spatial streams • MRC • 802.11ac beamforming • 20-, 40-, and 80-MHz channels • PHY data rates up to 1.3 Gbps (80 MHz in 5 GHz) • Packet aggregation: A-MPDU (Tx/Rx), A-MSDU (Tx/Rx) • 802.11 DFS • CSD support
802.11ac Wave 2 capabilities	<ul style="list-style-type: none"> • 4x4 MU-MIMO with three spatial streams • MRC • 802.11ac beamforming • 20-, 40-, 80, 160-MHz channels • PHY data rates up to 5.2 Gbps • Packet aggregation: A-MPDU (Tx/Rx), A-MSDU (Tx/Rx) • 802.11 DFS • CSD support
Integrated antenna	<p>Flexible radio (either 2.4 GHz or 5 GHz)</p> <ul style="list-style-type: none"> • 2.4 GHz, gain 4 dBi, internal antenna, omnidirectional in azimuth • 5 GHz, gain 6 dBi, internal directional antenna, elevation plane beamwidth 90° <p>Dedicated 5-GHz radio</p> <ul style="list-style-type: none"> • 5 GHz, gain 5 dBi, internal antenna, omnidirectional in azimuth
External antenna (sold separately)	<p>2802e Series access points are certified for use with antenna gains up to 6 dBi (2.4 GHz and 5 GHz)</p> <p>Cisco offers the industry's broadest selection of antennas, delivering optimal coverage for a variety of deployment scenarios</p>
Smart antenna connector	<p>Available on the 2802e Series access points only</p> <p>Requires the AIR-CAB002-DART-R= 2 ft smart antenna connector to RP-TNC connectors to</p>





	<p>connect a second antenna to the access point</p> <p>Required when running the flexible radio as either a second 5-GHz serving radio or Wireless Security Monitoring radio</p>
Interfaces	<p>2802I/E</p> <ul style="list-style-type: none"> ◦ 2x100/1000BASE-T autosensing (RJ-45) <p>Management console port (RJ-45)</p> <p>USB 2.0 (enabled via future software)</p>
Indicators	<p>Status LED indicates boot loader status, association status, operating status, boot loader warnings, boot loader errors</p>
Dimensions (W x L x H)	<p>Access point (without mounting brackets): 2802I: 8.66" x 8.68" x 2.17", 2802E: 8.66" x 8.77" x 2.50"</p>
Weight	<p>Cisco Aironet 2802i</p> <p>3.53 lb (1.6 kg)</p> <p>Cisco Aironet 2802e</p> <p>4.6 lb (2.09 kg)</p>
Input power requirements	<p>802.3at PoE+, Cisco Universal PoE (Cisco UPOE®)</p> <p>802.3at power injector (AIR-PWRINJ6=)</p>
Power draw	<p>26W at the PSE with all features enabled except for the USB 2.0 port</p> <p>30W at the PSE with the USB 2.0 port enabled</p>
Environmental	<p>Cisco Aironet 2802i</p> <ul style="list-style-type: none"> • Nonoperating (storage) temperature: -22° to 158°F (-30° to 70°C) • Nonoperating (storage) altitude test: 25°C, 15,000 ft. • Operating temperature: 32° to 104°F (0° to 40°C) • Operating humidity: 10% to 90% (noncondensing) • Operating altitude test: 40°C, 9843 ft. <p>Cisco Aironet 2802e</p> <ul style="list-style-type: none"> • Nonoperating (storage) temperature: -22° to 158°F (-30° to 70°C) • Nonoperating (storage) altitude test: 25°C, 15,000 ft. • Operating temperature: -4° to 122°F (-20° to 50°C) • Operating humidity: 10% to 90% (noncondensing) <p>Operating altitude test: 40°C, 9843 ft.</p>
System memory	<p>1024 MB DRAM</p> <p>256 MB flash</p>
Warranty	<p>Limited lifetime hardware warranty</p>





Want to Buy

Get a Quote



[Learn More](#) about Hi-Network



[Search](#) our Resource Library



[Follow](#) us on LinkedIn



Contact for [Sales or Support](#)

Contact HI-NETWORK.COM For Global Fast Shipping

HongKong Office Tel: +00852-66181601

HangZhou Office Tel: +0086-571-86729517

Email: info@hi-network.com

Skype: [echo.hinetwork](https://www.skype.com/people/echo.hinetwork)

WhatsApp Business: +8618057156223

