

Overview

The Cisco C1300-24P-4G is a versatile and robust networking switch designed to meet the demands of growing network environments. It features 24x 10/100/1000 PoE+ ports with a power budget of 195W, allowing for seamless connectivity and power supply to various devices. Additionally, it supports 4x Gigabit SFP uplink ports, making it an ideal choice for business applications requiring high performance and reliability.

Quick Specification

Table 1 shows the quick specification.

Model	C1300-24P-4G
Dimension	445 x 299 x 44 mm (17.5 x 11.77 x 1.73 in)
Weight	3.53 kg (7.78 lb)
Operating Temperature	23° to 122°F (-5° to 50°C)
Operating Humidity	10% to 90%, relative, noncondensing
Ports	24x 10/100/1000 PoE+ ports with 195W power budget
Combo Ports	4x Gigabit SFP
Form Factor	Fixed Configuration

Figure 1 shows the appearance of C1300-24P-4G.





Product Details

Product Features

- 24 high-performance 10/100/1000 PoE+ ports
- 195W total PoE power budget
- 4x Gigabit SFP uplink ports
- Advanced security features
- Energy-efficient design

Product Applications

- Enterprise network environments needing robust connectivity and performance.
- Medium-sized businesses requiring efficient power management for connected devices.
- Organizations looking for secure and scalable network infrastructure.

Supported Options

Accessory	Model
Cisco SFP Module	GLC-LH-SMD
Power Supply	PWR-C1-350WAC
Mounting Kit	RCKMNT-19-CMPCT

Compare to Similar Items

Model	Differences
Cisco C9200L-24P-4X	Higher power budget at 370W, 4x 10G SFP+ uplink ports
Cisco C1000-24P-4G-L	Lower power budget at 195W, supports only Layer 2 features
Cisco SG350-28P	Managed switch with additional features, PoE power budget at 195W

Get More Information

Do you have any questions about the C1300-24P-4G?

Contact us now via info@hi-network.com.





Specification

C1300-24P-4G Datasheet	
Ports	24x 10/100/1000 PoE+ ports with 195W power budget
Combo Ports	4x Gigabit SFP
Mounting	Rack-mountable
Forwarding Rate	41.66 Mpps
Switching Capacity	56.0 Gbps
Power	100-240V 50-60 Hz, internal, universal
PoE	Supported
Dimension	445 x 299 x 44 mm (17.5 x 11.77 x 1.73 in)
Weight	3.53 kg (7.78 lb)
Operating Temperature	23° to 122°F (-5° to 50°C)
Operating Humidity	10% to 90%, relative, noncondensing
Console port	Cisco standard RJ-45 console port and USB Type C port
USB port	USB Type C port on the front panel of the switch for easy file and image management as well as console port
Buttons	Reset button
Cabling type	Unshielded Twisted Pair (UTP) Category 5e or better for 1000BASE-T
LEDs	System, Link/Act, PoE, Speed
Flash	512 MB
CPU	ARM dual-core at 1.4 GHz
DRAM	1 GB DDR4
Certifications	UL (UL 62368), CSA (CSA 22.2), CE mark, FCC Part 15 (CFR 47) Class A

Want to Buy

Get a Quote

[Learn More](#) about Hi-Network[Search](#) our Resource Library[Follow](#) us on LinkedInContact for [Sales or Support](#)



Contact HI-NETWORK.COM For Global Fast Shipping

HongKong Office Tel: +00852-66181601

HangZhou Office Tel: +0086-571-86729517

Email: info@hi-network.com

Skype: echo.hinetwork

WhatsApp Business: +8618057156223

