



[Get a Quote](#)

Overview

The Cisco® 100GBASE CFP2 modules offer customers 100 Gigabit Ethernet connectivity options for data center networking, enterprise core aggregation, and service provider transport applications.

Quick Specification

Product Code	CFP2-100G-ER4=
Description	Cisco 100GBASE-ER4 CFP2 Module for SMF (<40 km)
Dimensions	144.8 x 82 x 13.6 mm
Wavelength (nm)	1310 band(LAN-WDM)
Fiber Type	SMF
Core Size (microns)	G.652
Modal Bandwidth (MHz-km)	\
Max Distance	40 km
Digital Optical Monitoring (DOM)	Yes



Product Details:

The Front Panel:



Cisco 100GBASE CFP2 Modules provide these highlights:

- Supports 100GBASE Ethernet and OTU3 rates.
- Hot-swappable input-output device that plugs into an Ethernet CFP2 port of a Cisco switch or router
- Provides flexibility of interface choice
- Supports “pay-as-you-populate” model
- Supports digital optical monitoring (DOM)
- Supports the Cisco quality identification (ID) feature, which enables a Cisco switch to identify whether the module is certified and tested by Cisco

Compare to Similar Items

Parameters	CFP2-100G-ER4=	CFP-100G-ER4=	CFP-100G-LR4=	CFP-100G-SR10=
Description	Cisco 100GBASE-ER4 CFP2 Module for SMF (<40 km)	Cisco 100GBASE-ER4 CFP Module for SMF (<40 km)	Cisco 100GBASE-LR4 CFP Module for SMF (<40 km)	Cisco 100GBASE-SR10 CFP Module for MMF (<40 km)
Dimensions	144.8 x 82 x 13.6 mm	144.8 x 82 x 13.6 mm	144.8 x 82 x 13.6 mm	144.8 x 82 x 13.6 mm
Wavelength (nm)	1310 band(LAN-WDM)	1310 band (LAN-WDM)	1310 band (LAN-WDM)	850
Fiber Type	SMF	SMF	SMF	MMF
Core Size (microns)	G.652	G.652	G.652	50 50
Modal Bandwidth (MHz-km)	\	\	\	2000 (OM3) 4700 (OM4)



Max Distance	40 km	40 km	10 km	100 m 150 m
Digital Optical Monitoring (DOM)	Yes	Yes	Yes	NO

Get more information:

Do you have any question about the CFP2-100G-ER4=?

Contact us now via e-mail: info@hi-network.com

Specific Data Sheet:

Description	Cisco 100GBASE-ER4 CFP2 Module for SMF (<40 km)
Dimensions	144.8 x 82 x 13.6 mm
Wavelength (nm)	1310 band(LAN-WDM)
Fiber Type	SMF
Core Size (microns)	G.652
Modal Bandwidth (MHz-km)	\
Max Distance	40 km
Digital Optical Monitoring (DOM)	Yes
Average Transmit Power (dBm)	Max:2.9 per lane Min:-2.9 per lane
Average Receive Power (dBm)	Max:4.5 per lane Min:-20.9 per lane
Transmit and Receive Wavelength	Four lanes: 1295.6 nm, 1300.1 nm, 1304.6 nm, and 1309.1 nm
Environmental Conditions and Power Requirements	
Operating temperature	32 to 158°F (0 to 70°C)
Storage temperature	-40 to 185°F (-40 to 85°C)
Maximum power consumption	8 W

Want to Buy

Get a Quote





[Learn More](#) about Hi-Network



[Search](#) our Resource Library



[Follow](#) us on LinkedIn



Contact for [Sales or Support](#)

Contact HI-NETWORK.COM For Global Fast Shipping

HongKong Office Tel: +00852-66181601

HangZhou Office Tel: +0086-571-86729517

Email: info@hi-network.com

Skype: [echo.hinetwork](https://www.skype.com/addtocontactlist/echo.hinetwork)

WhatsApp Business: +8618057156223

