Get a Quote



Overview

The MA5800-X17 is a HUAWEI GPON OLT, featuring 2x H901MPLA, 2x H901PILA and FAN modules. This high-performance OLT is designed to deliver a wide range of services and applications for broadband access networks, such as IPTV, VoIP, and high-speed internet access.

	- 4. 1			The second s	The second se	The second second	- A 12	Internation of the	HILL H	- 1.11	- Aunta		1.1.1.1.1	1 1 1	14111	The state of the s	
0				I				q	1								
		l	l	l				1.0									l
		l	l	l				E E E	1.2.2								
		l	l	l				ĥ	ĥ								l

								-3	Fan	tra;	Υ								
18 Universal board		2	3	*	5		7		9	10	11	12	C1	14	15	16	13	81	61
19 Powerl board	Service board	Service board	Service board	Service board	Service board	Service board	Service board	Service board	Control board	Control board	Service board								
0 Power board																			

Slot Type	Slot No.	Total				
Control board (SCU) slot	9,10	2				
Power board slot	20,21	2				
Universal interface board (GPIO) slot	0	1				
Service board slot	1~8,11~19	17				

Quick Specification

Model	Huawei SmartAX MA5800-X17
Maximum weight(including mounting brackets)	35 kg
Dimensions (H x W x D)	493 mm x 287 mm x 486 mm

Buy Huawei, Cisco, Zte, Hpe, Dell, Fortinet Network Equipment Online In China At Low Price! www.hi-network.com



SmartAX MA5800-X17 Datasheet

Get a Quote



Working voltage range	-38.4V DC to -72V DC
MPLS & PWE3	MPLS LDP, MPLS RSVP-TE, MPLS OAM, MPLS BGP IP VPN, tunnel
	protection switching, TDM/ETH PWE3, and PW protection switching
IPv6	IPv4/IPv6 dual stack, IPv6 L2 and L3 forwarding, and DHCPv6 relay
Multicast	IGMP v2/v3, IGMP proxy/snooping, MLD v1/v2, MLD Proxy/Snooping, and
municast	VLAN-based IPTV multicast

Product Details:

The Front Panel:



Features Huawei SmartAX MA5800-X17 provides:

★ Distributed architecture

Huawei SmartAX MA5800 X17 OLT is the industry's first distributed architecture OLT. The single-slot can support 10 GPON nonblocking access. It can smoothly evolve to support 50G PON. It can realize forwarding functions such as MAC and IP address without replacing the main control board.

★ 4K/8K/VR video experience

Huawei SmartAX MA5800 X17 OLT can meet 16,000 homes and enjoy ultra-high-definition 4K/8K/VR video online. By using a distributed cache, with larger cache and video burst absorption capability, therefore help 4K/8K/VR video quick start or channel switching

 \star Multi-service virtualization common platform

Huawei SmartAX MA5800 X17 OLT has the intelligence and virtualization capabilities to logically fragment devices and network resources, virtualize one OLT into multiple OLTs, and assign different virtual OLTs to different services such as homes. , enterprise, Internet of Things and other multi-service intelligent operations.

Buy Huawei, Cisco, Zte, Hpe, Dell, Fortinet Network Equipment Online In China At Low Price! www.hi-network.com



SmartAX MA5800-X17 Datasheet





Get more information: Do you have any question about SmartAX MA5800-X17? Contact us now via e-mail: <u>info@hi-network.com</u>

Specific Data Sheet:

Model	Huawei SmartAX MA5800-X17						
Dimensions (W x D x H)	493 mm x 287 mm x 486 mm						
Switching Capacity of the System	7 Tbit/s						
	272 x GPON/EPON						
	816 x GE/FE						
Maximum Number of Ports in a Subrack	136 x 10G GPON/10G EPON						
	136 x 10G GE						
	544 x E1						
	-40°C to 65°C*						
Ambient Temperature	*: The MA5800 can start up at a lowest temperature of -25°C and run at -40°C						
	65°C temperature refers to the highest temperature measured at the air intake vent						
Working Voltage Range	-38.4V DC to -72V DC						
	VLAN + MAC forwarding, SVLAN + CVLAN forwarding, PPPoE+, and DHCP						
Layer 2 Features	option82						
Layer 3 Features	Static route, RIP/RIPng, OSPF/OSPFv3, IS-IS, BGP/BGP4+, ARP, DHCP relay,						
Layer 5 realures	and VRF						
MPLS & PWE3	MPLS LDP, MPLS RSVP-TE, MPLS OAM, MPLS BGP IP VPN, tunnel						
	protection switching, TDM/ETH PWE3, and PW protection switching						
IPv6	IPv4/IPv6 dual stack, IPv6 L2 and L3 forwarding, and DHCPv6 relay						
	IGMP v2/v3, IGMP proxy/snooping, MLD v1/v2, MLD Proxy/Snooping, at						
Multicast	VLAN-based IPTV multicast						
	Traffic classification, priority processing, trTCM-based traffic policing, WRED,						
QoS	traffic shaping, HqoS, PQ/WRR/PQ + WRR, and ACL						
	GPON type B/type C protection, 10G GPON type B protection, BFD, ERPS						
	(G.8032), MSTP, intra-board and inter-board LAG, In-Service Software Upgrade						
System Reliability	(ISSU) of the control board, 2 control boards and 2 power boards for redundancy						
	protection, in-service board fault detection and rectification, and service overload						
	control						



SmartAX MA5800-X17 Datasheet

Get a Quote



Want to Buy



Contact HI-NETWORK.COM For Global Fast Shipping

HongKong Office Tel: +00852-66181601 HangZhou Office Tel: +0086-571-86729517 Email: info@hi-network.com Skype: echo.hinetwork WhatsApp Business: +8618057156223

